## Saskatoon Scissor Lift License

Saskatoon Scissor Lift License - The is an inherent chance in operating a scissor lift, since with all kinds and types of powered work tools will need proper handling in order to prevent accidents which can cause injuries or damage. Companies must make certain that employees using this machine have the needed training.

Businesses should not allow scissor lifts to be utilized by unskilled people. The scissor lift is used to lift individuals to high levels. Failure to know and fully abide by safety standard can result in injuries for the users or damage to the lift.

For scissor lift users, there is no legislation governing the use of fall protection. Then again, manufacturers can suggest the use of fall protection and in several cases tying off in scissor lifts might be required by employer rules, job-specific risk assessments or local rules.

To be able to make certain that the scissor lift is in good working condition prior to using the machinery, the operator should perform a thorough check. This is the operator's job, even though the unit has already been in service that day. The machine's operator's instruction manual contains a pre-operation checklist.

The things that an operator should look for when doing a scissor lift check, consists of checking tire-inflation pressure, and checking ground controls and platform controls in order to ensure they are functioning. Watch for any delayed movement on the fly section when the boom is retracting and extending since this may indicate some loose cables. While operating the controls, make sure that the emergency stop switches are working. Operate functions against the machine's cutout switches. Check the boom control system by cycling a boom lift to the furthest extent of its operating envelope. Safety limiters must automatically stop the unit before it moves into an unstable position, if they are working properly. If they aren't, shut down the lift and ensure that it is fixed before using it again.

Proper and safe operating measures must be followed at all times. Levers must be operated with controlled, even pressure. A control lever must never be pushed from one position to the opposite position. The lever must be shifted to neutral, prior to stopping, and then proceeding in the desired direction. When released, control switches and levers should automatically return to the neutral position. Depress the foot switch before operating platform controls.